Memory

e-MMC

e-MMC is a family of NAND flash memories with control functionality such as ECC, wear leveling and bad-block management.

e-MMC also provides a high-speed memory card interface compliant with JEDEC Version 5.0/5.1, eliminating the need for users to be concerned about directly controlling NAND flash memories. Thus, e-MMC can easily be used as a storage device for embedded applications.

Product list of e-MMC

		Class	e-MMC Version	Max Data Rate (MB/s)	Supply Voltage		Operating	Package	
Capacity	Part Number				V∝ (V)	Vccc (V)	Temperature (°C)	Size (mm)	Code
4GB	THGBMNG5D1LBAIT	Consumer	5.0	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11×10×0.8	P- WFBGA153- 1110-0.50
	THGBMNG5D1LBAIL	Consumer	5.0	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P- WFBGA153- 1113-0.50
8GB	THGBMJG6C1LBAIL	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P- WFBGA153- 1113-0.50
OOD	THGBMJG6C1LBAU7	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 ⁽¹⁾	11.5×13×1.0	P- VFBGA153- 1113-0.50
	THGBMJG7C1LBAIL	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P- WFBGA153 1113-0.50
16GB	THGAMRG7T13BAIL*	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×0.8	P- WFBGA153- 1113-0.50
	THGBMJG7C2LBAU8	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 (1)	11.5×13×1.2	P- TFBGA153- 1113-0.50
	THGBMJG8C2LBAIL	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-25 to 85	11.5×13×0.8	P- WFBGA153- 1113-0.50
32GB	THGAMRG8T13BAIL*	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×0.8	P- WFBGA153 1113-0.50

		THGBMJG8C4LBAU8	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 (1)	11.5×13×1.2	P- TFBGA153- 1113-0.50
64GB	CACB	THGAMRG9T23BAIL*	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85	11.5×13×0.8	P- WFBGA153- 1113-0.50
	THGBMJG9C8LBAU8	Industrial	5.1	400	2.7 to 3.6	1.70 to 1.95, 2.7 to 3.6	-40 to 105 (1)	11.5×13×1.2	P- TFBGA153- 1113-0.50	
	128GB	THGAMRT0T43BAIR*	Consumer	5.1	400	2.7 to 3.6	1.70 to 1.95	-25 to 85		P- VFBGA153- 1113-0.50

- Note (1): Tc=115°C max.
- * New Product: Contact the KIOXIA Corporation's sales representative for sample schedule about new products.
- Details about your intended usage would be checked before submitting samples of the Industrial class product.

Links

MLC/NAND Flash Memory

- e-MMC
- UFS
- e-MMC/UFS for Automotive Information & Entertainment Systems

Open in new window. • Open (PDF) in new window.

Business > Memory > NAND Flash Memories with an Integrated Controller > e-MMC

Home About Business Personal KIOXIA Global site

(KIOXIA Holdings Corporation)

About About UsMemory News

BusinessEvents SSD Sustainability
PersonalNews Where to Buy

Product & Technology
News

About Us

News

Contact Us | Privacy Policy | Terms and Conditions

Copyright © 2019 KIOXIA Corporation. All Rights Reserved.