

# 6x30mm Fast-Acting Glass Fuse



## Product Details

### Overview

#### Quick Details

Place of Origin: Guangdong, China (Mainland)

Usage: Low Voltage

Breaking Capacity: High

Safety Standards: UL CSA VDE CCC

Fuse type: glass fuse

Tube material: Glass

Current rating : 0.1A 0.5A 1A 2A 3A 5A 10A 15A 20A 30A 40A

Size: 6x30

Voltage : 250V AC/DC

Conductor: copper

Colors: White, clear etc

Operating Temperature: -55C ~ 125C

### Description:

Glass fuse : 6x30

Standard Package: 1,000

Category: Circuit Protection

Family: Fuses

Fuse Type: Cartridge, Glass  
 Current Rating: 100mA ~ 20A  
 Voltage Rating - AC: 250V  
 Voltage Rating - DC: 250V  
 Response Time: Fast  
 Package / Case: 6mm x 30mm  
 Mounting Type: Holder  
 Breaking Capacity @ Rated Voltage: 50A  
 Melting I<sup>2</sup>t: 95  
 Approvals: CE, CSA, IMQ, SEMKO, UL, VDE  
 Operating Temperature: -55°C ~ 125°C  
 Size / Dimension: 3 L (6.10mm x 30.00mm)  
 Packaging: Bulk  
 DC Cold Resistance: 0.011 Ohm

Fuse Type	Current Rating	Voltage Rating-AC/DC	Package / Case	RoHS
Cartridge, Glass	1A	250V	6mm x 30mm	RoHS
Cartridge, Glass	2.5A	250V	6mm x 30mm	RoHS
Cartridge, Glass	250mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	3A	250V	6mm x 30mm	RoHS
Cartridge, Glass	500mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	5A	250V	6mm x 30mm	RoHS
Cartridge, Glass	4A	250V	6mm x 30mm	RoHS
Cartridge, Glass	2A	250V	6mm x 30mm	RoHS
Cartridge, Glass	3.5A	250V	6mm x 30mm	RoHS
Cartridge, Glass	600mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	375mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	800mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	100mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	7A	250V	6mm x 30mm	RoHS
Cartridge, Glass	750mA	250V	6mm x 30mm	RoHS
Cartridge, Glass	1.6A	250V	6mm x 30mm	RoHS
Cartridge, Glass	6.3A	250V	6mm x 30mm	RoHS
Cartridge, Glass	6A	250V	6mm x 30mm	RoHS
Cartridge, Glass	8 A	250V	6mm x 30mm	RoHS
Cartridge, Glass	10A	250V	6mm x 30mm	RoHS
Cartridge, Glass	15A	250V	6mm x 30mm	RoHS
Cartridge, Glass	20A	250V	6mm x 30mm	RoHS

## Features

- Halogen Free

## Applications:

- Power Supplies
- Battery charger
- Monitor
- Adapter

## Specifications

- Breaking Capacity @ Rated Voltage:35A ~ 10000A
- Current Rating:100mA ~ 20A
- DC Cold Resistance:0.013 Ohm ~ 11.9 Ohm
- Fuse Type : Cartridge, Glass
- Melting I<sup>2</sup>t:0.02 ~ 750
- Mounting Type : Holder
- Operating Temperature:-55°C ~ 125°C
- Package / Case: 6mm x 30mm
- Packaging : Bulk
- Response Time : FAST
- Size / Dimension : (6.10mm x 30.00mm)
- Voltage Rating - AC:125V ~ 250V

## Features:

1. We are certificated by ISO9001 UL DVE REACH.
2. Assembled according to customers' specifications.
3. Technology process: cutting , crimping, welding, assembly and testing.
4. Buyer's specifications are accepted.
5. 100%tested before shipment.
6. Stable quality, high reliability.