

Two 7 segments 0.28 inch LED display Green light common anode



Brief introduction of LED digital tube

- 1, product name: CL2821 BB
- 2, word number: 2
- 3, screen size: 0.28 inches
- 4, bright color: Blue; (other colors can be customized)
- 5.8 word height: 0.28
- 6. Outline dimension: 15.02mm * 10.00mm * 5.00mm
- 7, public foot: 9-6
- 8, total PIN number: 10 pins
- 9 Polarity: Common anode
- 10, surface color: black panel
- 11, Source color: red / Green / blue / white / orange
- 12, colloidal color: milky white



极限参数 (Limited Parameters)

参数 Parameters	符号 Symbol	极限参数 Limited parameter 100mA 20mA		
肽冲电流 Peak Forward Current	lfp			
直流电缆 Continuous Forward Current	If			
反向电压 Reverse Voltage	Vr	5V		
工作温度 Operating temperature Range	Topr	-30 to +70°C		
储存温度 Storage temperature Range	Tstg	-40 to -85°C		

光电参数(Photoelectric Parameters)

参数 Parameter	正向电压 Forward voltage		反向电流 Reverse current		发光强度 Luminous Intensity	波长 Wavelength	功耗 Power consumption
符号 Name	VF		IR.		IV	λρ	Pt
単位 Unit	V		uA		med	nm	mW
	IF=20 mA		VR=5V		IF=20mA	IF=20mA	IF=20mA
条件 Condition	平均 Arranga	最大 Max	부회 Amange	最大 Max.	平道; Amange	平当) Amange	부리; Arrange
高亮紅 High red R	2	2.4		20	45	628	36
黄绿色 Yellow green G	2.2	2.6	**	20	11	571	44
黄色 Yellow Y	2,1	2.5		20	85	590	42
蓝色 Blue B	3.3	4		20	12	465	66
琴绿色 Pure green PG	3.3	4		20	220	51.5	66
白色 White W	3.3	4		20			66