
P-Channel Enhancement Mode MOSFET

Features

- -30V/-6A , $R_{DS(ON)}$=95mΩ(typ.) @ V_{GS}=-10V
  $R_{DS(ON)}$=140mΩ(typ.) @ V_{GS}=-4.5V
- Super High Dense Cell Design for Extremely Low $R_{DS(ON)}$
- Reliable and Rugged
- TO-252 Package


Pin Description



Top View of TO-252

Applications

- Power Management in Notebook Computer , Portable Equipment and Battery Powered Systems.



P-Channel MOSFET

Ordering and Marking Information

APM3095P □□-□□

- Handling Code
- Temp. Range
- Package Code

Package Code
U : TO-252
Operating Junction Temp. Range
C : -55 to 150°C
Handling Code
TU : Tube
TR : Tape & Reel

APM3095P U :



XXXXX - Date Code

Absolute Maximum Ratings (T$_A$ = 25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
V_{DSS}	Drain-Source Voltage	-30	V
V_{GSS}	Gate-Source Voltage	±25	
I_D*	Maximum Drain Current – Continuous	-12	A
I_{DM}	Maximum Drain Current – Pulsed	-30	

* Surface Mounted on FR4 Board, t ≤ 10 sec.

ANPEC reserves the right to make changes to improve reliability or manufacturability without notice, and advise customers to obtain the latest version of relevant information to verify before placing orders.

Copyright © ANPEC Electronics Corp.

Rev. A.1 - Oct., 2002

Absolute Maximum Ratings Cont. (T_A = 25°C unless otherwise noted)

Symbol	Parameter		Rating	Unit
P_D	Maximum Power Dissipation	T_A=25°C	50	W
		T_A=100°C	20	
T_J	Maximum Junction Temperature		150	°C
T_{STG}	Storage Temperature Range		-55 to 150	°C
$R_{\theta jA}$	Thermal Resistance – Junction to Ambient		50	°C/W

Electrical Characteristics (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	APM3095P			Unit
			Min.	Typ.	Max.	
Static						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V , I_{DS}=-250μA	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-24V , V_{GS}=0V			-1	μA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} , I_{DS}=-250μA	-1	-1.5	-2	V
I_{GSS}	Gate Leakage Current	V_{GS}=±25V , V_{DS}=0V			±100	nA
$R_{DS(ON)}$[a]	Drain-Source On-state Resistance	V_{GS}=-10V , I_{DS}=-6A		95	110	mΩ
		V_{GS}=-4.5V , I_{DS}=-3A		140	160	
V_{SD}[a]	Diode Forward Voltage	I_{SD}=-1.25A , V_{GS}=0V		-0.7	-1.3	V
Dynamic[b]						
Q_g	Total Gate Charge	V_{DS}=-15V , I_{DS}=-3A		8	13	nC
Q_{gs}	Gate-Source Charge	V_{GS}=-10V		1.9		
Q_{gd}	Gate-Drain Charge			1.1		
$t_{d(ON)}$	Turn-on Delay Time	V_{DD}=-15V , I_{DS}=-1A , V_{GEN}=-10V , R_G=6Ω R_L=15Ω		10	20	ns
T_r	Turn-on Rise Time			8	20	
$t_{d(OFF)}$	Turn-off Delay Time			25	50	
T_f	Turn-off Fall Time			5	15	
C_{iss}	Input Capacitance	V_{GS}=0V V_{DS}=-25V Frequency=1.0MHz		550		pF
C_{oss}	Output Capacitance			120		
C_{rss}	Reverse Transfer Capacitance			75		

Notes


[a] : Pulse test ; pulse width ≤300μs, duty cycle ≤ 2%

[b] : Guaranteed by design, not subject to production testing


Copyright © ANPEC Electronics Corp.

Typical Characteristics


Output Characteristics




Transfer Characteristics



Threshold Voltage vs. Junction Temperature




On-Resistance vs. Drain Current




Copyright © ANPEC Electronics Corp.

Typical Characteristics


On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature



Gate Charge




Capacitance




Copyright © ANPEC Electronics Corp.

Typical Characteristics


Source-Drain Diode Forward Voltage



Single Pulse Power




Normalized Thermal Transient Impedence, Junction to Ambient



Packaging Information

TO-252(Reference JEDEC Registration TO-252)



Dim	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.18	2.39	0.086	0.094
A1	0.89	1.27	0.035	0.050
b	0.508	0.89	0.020	0.035
b2	5.207	5.461	0.205	0.215
C	0.46	0.58	0.018	0.023
C1	0.46	0.58	0.018	0.023
D	5.334	6.22	0.210	0.245
E	6.35	6.73	0.250	0.265
e1	3.96	5.18	0.156	0.204
H	9.398	10.41	0.370	0.410
L	0.51		0.020	
L1	0.64	1.02	0.025	0.040
L2	0.89	2.032	0.035	0.080


Copyright © ANPEC Electronics Corp.

Physical Specifications

Terminal Material	Solder-Plated Copper (Solder Material : 90/10 or 63/37 SnPb)
Lead Solderability	Meets EIA Specification RSI86-91, ANSI/J-STD-002 Category 3.

Reflow Condition (IR/Convection or VPR Reflow)

Reference JEDEC Standard J-STD-020A APRIL 1999



Classification Reflow Profiles

	Convection or IR/ Convection	VPR
Average ramp-up rate(183°C to Peak)	3°C/second max.	10 °C /second max.
Preheat temperature 125 ± 25°C)	120 seconds max.	
Temperature maintained above 183°C	60 ~ 150 seconds	
Time within 5°C of actual peak temperature	10 ~ 20 seconds	60 seconds
Peak temperature range	220 +5/-0°C or 235 +5/-0°C	215~ 219°C or 235 +5/-0°C
Ramp-down rate	6 °C /second max.	10 °C /second max.
Time 25°C to peak temperature	6 minutes max.	

Package Reflow Conditions


pkg. thickness ≥ 2.5mm and all bags	**pkg. thickness < 2.5mm and pkg. volume ≥ 350 mm³**	**pkg. thickness < 2.5mm and pkg. volume < 350mm³**
Convection 220 +5/-0 °C		Convection 235 +5/-0 °C
VPR 215-219 °C		VPR 235 +5/-0 °C
IR/Convection 220 +5/-0 °C		IR/Convection 235 +5/-0 °C

Copyright © ANPEC Electronics Corp.

Reliability test program

Test item	Method	Description
SOLDERABILITY	MIL-STD-883D-2003	245°C,5 SEC
HOLT	MIL-STD 883D-1005.7	1000 Hrs Bias @ 125°C
PCT	JESD-22-B, A102	168 Hrs, 100% RH, 121°C
TST	MIL-STD 883D-1011.9	-65°C ~ 150°C, 200 Cycles

Carrier Tape & Reel Dimensions



Application	A	B	C	J	T1	T2	W	P	E
TO-252	330 ±3	100 ± 2	13 ± 0. 5	2 ± 0.5	16.4 + 0.3 -0.2	2.5± 0.5	16+ 0.3 - 0.1	8 ± 0.1	1.75± 0.1
	F	D	D1	Po	P1	Ao	Bo	Ko	t
	7.5 ± 0.1	1.5 +0.1	1.5± 0.25	4.0 ± 0.1	2.0 ± 0.1	6.8 ± 0.1	10.4± 0.1	2.5± 0.1	0.3±0.05

Copyright © ANPEC Electronics Corp.

Cover Tape Dimensions

Application	Carrier Width	Cover Tape Width	Devices Per Reel
TO- 252	16	13.3	2500

Customer Service

Anpec Electronics Corp.
Head Office :
5F, No. 2 Li-Hsin Road, SBIP,
Hsin-Chu, Taiwan, R.O.C.
Tel : 886-3-5642000
Fax : 886-3-5642050
Taipei Branch :
7F, No. 137, Lane 235, Pac Chiao Rd.,
Hsin Tien City, Taipei Hsien, Taiwan, R. O. C.
Tel : 886-2-89191368
Fax : 886-2-89191369

Copyright © ANPEC Electronics Corp.