

GERMANIUM POWER TRANSISTORS

Type Number	Case Type	V_{CE0} V	V_{CE1} V	V_{CE2} V	V_{CE3} V	V_{CE4} V	CURRENT GAIN		V_{CE1} V	I_C A	SATURATION VOLTAGES		θ_{JA} °C/W
							h_{FE} Min.	h_{FE} Max.			V_{CE1} V	V_{BE1} V	

4 AMP GERMANIUM PNP

2N234A	TO-3	25			25	25	25	34	40	2.0			
2N235B	TO-3	25		15.0	35	35	34	40	2.0	2.0			
2N255A	TO-3	15		15.0	15	25	25	25	2.0	2.0			
2N256A	TO-3	30		15.0	25	25	25	25	2.0	2.0			
2N257	TO-3	40		6.0	25	20	20		2.0	2.0			
2N553	TO-3	80		40.0		40	80	75	2.0	.5	.90	.3	2.00
2N663	TO-3	50	25	20.0		25	75	2.0	3.0	1.00	1.50	.3	1.20
2N1159	TO-3	80	60	20.0		30	75	2.0	3.0	.07		3.0	1.20


5 AMP GERMANIUM PNP

2N350	TO-3	50		10.0		30	20	60	2.0	.7	.40	3.0	.300	.80
2N350A	TO-3	50		25.0		40	20	60	2.0	.7	1.75	3.0	.300	.80
2N351	TO-3	50		10.0		30	25	90	2.0	.7	.40	3.0	.300	.80
2N351A	TO-3	50		25.0		40	25	90	2.0	.7	1.75	4.0	.400	.80
2N376	TO-3	50		10.0		30	35	120	2.0	.7	.40	3.0	.300	.80
2N376A	TO-3	50		25.0		40	35	120	2.0	.7	1.75	5.0	.500	.80
2N665	TO-3	80		40.0		40	40	80	2.0	.5	.90	.3	.200	1.00
2N669	TO-3	40		20.0		30	75	250	2.0	.5				.80
2N1011	TO-3	80	40	40.0		80	30	75	2.0	3.0	.15	3.0	.300	2.00
2N1168	TO-3	50		20.0		30	70	110	2.0	1.0	.25	3.0	.100	1.50
2N1529	TO-3	40	20	20.0		30	20	40	2.0	3.0	1.50	3.0	.300	1.20
2N1529A	TO-3	40	20	20.0		30	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1530	TO-3	60	30	30.0		45	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1530A	TO-3	60	30	30.0		45	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1531	TO-3	80	40	40.0		60	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1531A	TO-3	80		40.0		60	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1532	TO-3	100	50	50.0		75	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1532A	TO-3	100		50.0		75	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1533	TO-3	120	60	60.0		90	20	40	2.0	3.0	1.50	3.0	.300	.80
2N1534	TO-3	40	20	20.0		30	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1534A	TO-3	40		20.0		30	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1535	TO-3	60	30	30.0		45	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1535A	TO-3	60		30.0		45	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1536	TO-3	80	40	40.0		60	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1536A	TO-3	80		40.0		60	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1537	TO-3	100	50	50.0		75	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1537A	TO-3	100		50.0		75	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1538	TO-3	120	60	60.0		90	35	70	2.0	3.0	1.20	3.0	.300	.80
2N1539	TO-3	40	20	20.0		30	50	100	2.0	3.0	.30	3.0	.300	.80
2N1539A	TO-3	40		20.0		30	50	100	2.0	3.0	.30	3.0	.300	.80
2N1540	TO-3	60	30	30.0		45	50	100	2.0	3.0	.30	3.0	.300	.80
2N1540A	TO-3	60		30.0		45	50	100	2.0	3.0	.30	3.0	.300	.80
2N1541	TO-3	80	40	40.0		60	50	100	2.0	3.0	.30	3.0	.300	.80
2N1541A	TO-3	80		40.0		60	50	100	2.0	3.0	.30	3.0	.300	.80
2N1542	TO-3	100	50	50.0		75	50	100	2.0	3.0	.30	3.0	.300	.80
2N1542A	TO-3	100		50.0		75	50	100	2.0	3.0	.30	3.0	.300	.80
2N1543	TO-3	120	60	60.0		90	50	100	2.0	3.0	.30	3.0	.300	.80
2N1543A	TO-3	120		60.0		90	50	100	2.0	3.0	.30	3.0	.300	.80
2N1544	TO-3	40	20	20.0		30	75	150	2.0	3.0	.20	3.0	.300	.80
2N1544A	TO-3	40	20	20.0		30	75	150	2.0	3.0	.20	3.0	.300	.80
2N1545	TO-3	60	30	30.0		45	75	150	2.0	3.0	.20	3.0	.300	.80
2N1545A	TO-3	60	30	30.0		45	75	150	2.0	3.0	.20	3.0	.300	.80
2N1546	TO-3	80	40	40.0		60	75	150	2.0	3.0	.20	3.0	.300	.80
2N1546A	TO-3	80	40	40.0		60	75	150	2.0	3.0	.20	3.0	.300	.80
2N1547	TO-3	100	50	50.0		75	75	150	2.0	3.0	.20	3.0	.300	.80
2N1547A	TO-3	100	50	50.0		75	75	150	2.0	3.0	.20	3.0	.300	.80
2N1548	TO-3	120	60	60.0		90	75	150	2.0	3.0	.20	3.0	.300	.80
2N1971	TO-3	80		40.0		25	60	2.0	.5					2.00
2N2266	MT-36	80	55			25	75	2.0	5.0	.75	5.50	5.0	.667	1.20
2N2267	MT-36	100	55			25	75	2.0	5.0	.75		5.0	.667	1.20

6 AMP GERMANIUM PNP

2N1136	TO-3	60		15.0	35		50	100	5.0	3.0	1.0	3.0	.300	1.20
2N1136A	TO-3	90		15.0	65		50	100	5.0	3.0	1.0	3.0	.300	1.20
2N1136B	TO-3	100		15.0	75		50	100	5.0	3.0	1.0	3.0	.300	1.20
2N1137	TO-3	60	25	15.0	35		75	150	5.0	3.0	1.0	3.0	.300	1.20
2N1137A	TO-3	90	55	15.0	65		75	150	5.0	3.0	1.0	3.0	.300	1.20

MODIFIED TO-3
(60 mil pins)



MT-36

