

H16127MCG



Toroidal Single Port Lan Transformer , SMD 16 Pinout H16127MCG

gigabit magnetics transformer

Specification:	H16127MCG	LINK-PP P/N:	LP1102NL
Speed:	10/100 BASE-T	Number Of Ports:	SINGLE
Application:	Lan Ethernet(NoN PoE)	Temperature:	0 TO + 70°C

Toroidal Single Port Lan Transformer , SMD 16 Pinout H16127MCG

Detailed Information:

LINK-PP LP1102NL 100% CROSS PULSE H16127MCG	
LINK-PP Part Number	LP1102NL
Pulse Part Number	H16127MCG
Speed	10/100BASE-T
Number of Ports	SINGLE
Application - LAN	ETHERNET (NoN PoE)
Package	SMD
Temperature	0°C TO +70°C
AutomDX	YES
Comment	SAME AS NL VERSION
Configuration RX	T,C,S
Configuration TX	T,C,S
Construction	OPEN FRAME
Cores Per Port	4
Package Height (Inches)	0.236
Package Height (mm)	5.994
Package Length (Inches)	0.451
Package Length (mm)	11.45
Package Width (Inches)	0.400
Package Width (mm)	10.20
Turns Ratio RX	1CT:1CT
Turns Ratio TX	1CT:1CT

