

BATTERY CHARGE DISPLAY



Car Battery Charge Level Indicator 12V 24V 36V 48V 60V 72V Lithium Battery Capacity Meter 0.56" LED Digital Voltmeter Tester

Description

Digital voltmeter 12-72V with red display ZX-EB120 VER. 5.0.

8 power levels: 10% 25% 40% 50% 60% 75% 90% 100% full

Working current: 5-15 ma

Refresh rate: 300mS once

Display mode: 0.56" three-digit LED digital tube

Voltage color: red

Wire length: about 20 cm

Dimensions: 48 x 29 x 22 mm

Mounting hole: 46 x 27 mm

Working temperature: -20°C~65°C

6V 12V 24V 36V 48V 60V 72V lead-acid battery.

Suitable for 36V, 48V, 60V lithium batteries

Lithium batteries, polymer batteries, nickel-metal hydride batteries, lead-acid batteries.

Cars, motorcycles, bicycles, trucks, etc.

Note:

Input voltage greater than 72V can be permanently damaged!

Your opinion matters!

Features:

1. Dual display power + voltage at a glance. The display is more intuitive. The upper eight-color bar (2 red, 6 green) shows the battery power. Downward voltmeter (battery voltage display), the decimal point of the voltmeter automatically moves to higher precision.
2. Wide range of use, can be used for lithium batteries, lead-acid batteries, car batteries, electric vehicle batteries and other types of batteries and electrical equipment. The principle of conventional voltage calculation is the same as the principle of the electric vehicle's power display meter.
3. The meter automatically recognizes voltage and electricity, and has reverse connection protection function (reverse connection will not burn).

Instructions for use: The meter head is a two-wire system, which can directly test the battery.

Tips: This scale is suitable for 12V, 24V, 36V, 48V, 60V battery cars, and can be used for lithium batteries, polymer batteries, and nickel-metal hydride batteries. Can also be used for other power/voltage measurement purposes.

Not suitable for: large trucks, cranes, forklifts and other high-power and high-load vehicles!

Specification:

Product model: 12-60V electric voltmeter

Product material: ABS material

Product color: black

Product size: 48x29x22mm(L*W*D); Lead length: 15cm

Packing size: 20*15*3cm

Product net weight: 20g

Product gross weight: 25g

Measuring range: 12V-96V

Input voltage: 0(V)

Output voltage: 60(V)

Ambient temperature: -10°C ~ 65°C

Voltage measurement error: $\pm 1\%$

8-stage battery: 10% 25% 40% 50% 60% 75% 90% full

Working current: 5--15ma

Refresh rate: about 300mS once

Display mode: 3 0.56" LED digital tube

Mounting hole: 46x27mm