BNC "T" Adapter

RoHS Compliant



Connector:

Type : BNC T Adapter

1× Male BNC 2× Female BNC

Electrical:

Voltage Rating: 500V ACNominal Impedance: 50ΩWithstanding Voltage: 1,500VrmsInsulation Resistance: 5,000MΩ min.Frequency Range: 0-4 GHz

Material:


Body/housing : Nickel plated phosfor bronze

Contacts : Brass

Gasket : Silicone Rubber

Dielectric : Delrin

Diagram



Dimensions: Millimetres (Inches)

No.	Description	Material	Finish
1	Body I	Brass	Nickel 100µ" Min.
2	Centre Contact I		Gold
3	Shell	Zinc	Nickel 100µ" Min.
4	Body II	Brass	
5	Insulation	POM	None
6	Gasket	Rubber	
7	Washer	Brass	
8	Spring Washer	SK-5	Nickel 100µ" Min.
9	Washer		
10	Centre Contact II	Brass	Gold
11	Washer		Nickel 100µ" Min.
12	Insulation	POM	None

Part Number Table

Description	
BNC T Adapter, 1 × Plug & 2 × Jack	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.