




成品确认书



面板移印图形参考文案



主要技术特性要求:

- 1.使用温度范围: -25~+85℃ (25T85)
- 2.额定工作电压、电流: 3A 250V AC
- 3.绝缘电阻: ≥100MΩ
- 4.接触电阻: ≤0.03Ω
- 5.耐压: AC150V(50Hz)/min
- 6.抗电强度: ≥1500V AC/min
- 7.寿命: 10000次

2.额定工作电压、电流：3A 250V AC 3.绝缘电阻：≥100MΩ 4.接触电阻：≤0.03Ω 5.耐压：AC150V(50Hz)/min 6.漏电强度：≥1500V AC/min 7.寿命：10000次				品质部/日期				5	灯泡	0	普通灯泡					
								4	盖子	1	PA66					
				生产部/日期				3	中铝通杆	2	黄铜	电镀铜棒				
								2	盖板	1	黄铜	电镀铜棒				
				审核/日期				1	底座	1	PA66					
序号	名称	数量	材 料					处 理	单件 质 量	总计	备 注					
A4				普通公差： COMMON TOLERANCE：												
A3																
A2				X.XX	±0.10	单位	mm	投影		品名	船型开关	比例	1：1			
A1				X.X	±0.15	绘图		核对		型号	KCD2-101					
				X	±0.25	日期		核准		图号	KCD1-114					

