KCD5-303 Inline Cord Switch SPST



• Specification

KCD5-303 Inline Cord Switch SPST

The KCD5-303 inline power cord switch SPST is perfect for when you just want a simple on/off switch that is included. Inside is a simple rocker switch with solder terminals with crimp stress relief. Connect some wires, solder them in place, and press the housing together, and you have a clean-looking switch. 303 inline switches are widely used in home lighting, such as desk lamps and floor lamps. The colors of white and black are standard colors. If you need other colors, please let me know and I will check and reply to you. For this switch, we have single port and dual port.

KCD5-303 Inline Cord Switch SPST datasheet below

Material:	PP	Color:	Standard black and white, other colors also available

Contact Configuration:	SPST/SPDT	Switch Operation:	ON-OFF
Rating:	2A 250VAC/3A 125VAC	Withstand voltage:	>=2500V/5S/0.025MA
Contact Resistance:	<0.02mΩ	Operating Temperature:	-40°C~+85°C
Insulation Resistance:	>=100mΩ	Electrical Life:	≥ 10,000 Cycles
Percussive voltage:	0.5NM±0.04NM	Combustibility:	94V lever2
Certification:	CE, CQC, SGS	OEM or ODM:	Available

产品性能一览 LIST OF PRODUCT PERFORMANCE

环境温度(Environmental temperature)	-40℃-+85℃	耐电压(Withstand voltage)	≥ 2500V/5S/0.025MA
额定电流、电压(Rating)	2A 250V / 3A 125VL	冲击电压(Percussive voltage)	0,5NM ± 0,04NM
接触电阻(Contact resistance)	≤ 0,02Ω	拉力测试(Tensile testing)	30N/min
绝缘电阻(Insulation resistance)	≥ 100MΩ	操作寿命(Operational life)	10000 次
介电强度(Dielectric strength)	≥ 1500VAC/min	燃烧性(Combustibility)	94V 2 级

外形图 OUTLINE 电路图 CIRCUIT





